

XBT SERIES Tube Extenders



Precise Sampling of Low Viscosity Oil from low or unpressurized systems

- ✓ Consistently sample active oil (up to VG 220) from gearboxes and reservoirs. Avoid problems caused by sedimentation or settled oil.
- ✓ Uses a compact reusable thread-on probe and disposable tubing to avoid cross contamination.
- ✓ Installs easily into drain, fill or sampling pipe ports.
- ✓ Flexible steel 3/16 SAE J527 tubing provides full flow with less purge time.
- ✓ Swivel options(-S) available for bent tubes in confined locations.
- ✓ Stainless steel valves (-R) , adapters and tubes (-TR) are available for extra corrosion resistance.

XBT Order Numbers:

Part#	Valve	Tube	Style	Length
XB14N	Steel, 16x2, 1/4" NPTF	None	NA	NA
XB14NRV	Stainless, 16x2, 1/4" NPTF	None	NA	NA
XB14NT12	Steel, 16x2, 1/4" NPTF	Steel 3/16"	Rigid	12"
XB14NT18	Steel, 16x2, 1/4" NPTF	Steel 3/16"	Rigid	18"
XB14NT24	Steel, 16x2, 1/4" NPTF	Steel 3/16"	Rigid	24"
XB14NTS12	Steel, 16x2, 1/4" NPTF	Steel 3/16"	Swivel	12"
XB14NTS18	Steel, 16x2, 1/4" NPTF	Steel 3/16"	Swivel	18"
XB14NTS24	Steel, 16x2, 1/4" NPTF	Steel 3/16"	Swivel	24"
XB14NTR12	Steel, 16x2, 1/4" NPTF	Stainless 3/16"	Rigid	12"
XB14NTR18	Steel, 16x2, 1/4" NPTF	Stainless 3/16"	Rigid	18"
XB14NTR24	Steel, 16x2, 1/4" NPTF	Stainless 3/16"	Rigid	24"
XB14NTRS12	Steel, 16x2, 1/4" NPTF	Stainless 3/16"	Swivel	12"
XB14NTRS18	Steel, 16x2, 1/4" NPTF	Stainless 3/16"	Swivel	18"
XB14NTRS24	Steel, 16x2, 1/4" NPTF	Stainless 3/16"	Swivel	24"
XB14NRTR12	Stainless, 16x2, 1/4" NPTF	Stainless 3/16"	Rigid	12"
XB14NRTR18	Stainless, 16x2, 1/4" NPTF	Stainless 3/16"	Rigid	18"
XB14NRTR24	Stainless, 16x2, 1/4" NPTF	Stainless 3/16"	Rigid	24"
XB14NRTRS12	Stainless, 16x2, 1/4" NPTF	Stainless 3/16"	Swivel	12"
XB14NRTRS18	Stainless, 16x2, 1/4" NPTF	Stainless 3/16"	Swivel	18"
XB14NRTRS24	Stainless, 16x2, 1/4" NPTF	Stainless 3/16"	Swivel	24"

Add V for Viton™ (B14NVT12)

Part#	Description
XSBF4	Sample Probe with barb and 8" 1/4" OD tube
XSR4	1/4" OD tubing roll (100 feet std)
X6N-14NF	3/8" NPTF Male Bushing
X8N-14NF	1/2" NPTF Male Bushing
X12N-14NF	3/4" NPTF Male Bushing

Probe Device



XSBF4, steel probe with 8" length of 1/4" OD tube (SR4).

Predictive Maintenance Corporation

8330 Decarie
 Montreal, Quebec, H4P-2P5
 Toll Free: 1-800-461-TEST
 Phone: 514-383-6330
 Fax: 514-383-5631
 tribologik@pmaint.com
 www.pmaint.com

Specifications

Spec	Value
Operating Pressure	500psi (35 bar)
Standard Nitrile Seal Temp	-40 to +250°F (-40 to +120°C)
Optional Viton Seal Temp	-25 to +400°F (-31 to +204°C)